

Counter Prep Station

Shallow Drawers + Solid Worktop



VLS2/CW

Standard Castors (C) Solid Worktop (W)

Hydrocarbon R600a Refrigerant

(also available in HFC R404a)



'B' Energy Rating in Freezer Mode

'A' Energy Rating in Fridge Mode (Consumption 325 kWh/annum)

Under Counter Prep Station Shallow Drawers + Cover Top



VLS2/CT Standard Castors (C) Cover top (T)

Storage Capacity

Gastronorm (GN) Pans

4 x 1/1 GN 75 mm Deep or equivalent (per Drawer)

Maximum Weight 30 kg of Food (per Drawer)

Volume 65 Litres (per Drawer)

Applications

- Bulk storage at the point of use
- Ideal for meat, deli and larder prep
- Suitable for pastry and dessert prep
- Perfect storage for garnish and and 'mise en place' generally
- Frozen storage next to deep fry station, with worktop mounted
 Fry Basket Rack as an optional extra

Temperature Flexibility

Foods can be stored at the optimum set point anywhere in the range



Climate Testing

Tested to Climate Class 4
(30°C & 55% relative humidity)
for temperature and energy
consumption and to Climate
Class 5 (40°C & 40% relative
humidity) for temperature

Electrical

Mains Supply 230 Vac 50 Hz

Power Socket (included)
Correct 2 or 3 Pin Plug
fitted for each country

Mains Lead (included)


2 Metre Coiled Lead

PREP STATION - COUNTER & UNDER COUNTER - SHALLOW DRAWER - SIDE ENGINE UNITS - VLS2 SERIES



Plan View |

Shallow Drawer Prep Station (VLS2) with Open Drawer





Extended Tops

Solid Worktops (W) can be extended up to 200 mm left & right and 150 mm back, to give more preparation space

Elevations |


Counter Prep Station Shallow Drawer (VLS2) Standard Castors (C) Solid Worktop (W)





Under Counter Prep Station Shallow Drawer (VLS2)

Standard Castors (C)
Cover top (T)



700

738


Double Drawer Module



Tops













Counter Prep Station Specifications

| | PREP STATION + OLID WORKTOP (W) | High Castor Base (HC) | | Standard Castor Base (C) | | Small Castor Base (SC) | | Rollers & Feet Base (R) | | Small Rollers & Feet Base (SR) | | Locking Roller Base (L) | | Small Locking Roller Base (SL) | |
|---|------------------------------------|--------------------------|----------|-----------------------------|----------|---------------------------|----------|----------------------------|----------|-----------------------------------|----------|----------------------------|----------|-----------------------------------|------------|
| | Finished Height | 855 mm | VLS2/HCW | 784 mm | VLS2/CW | 763 mm | 739 mm | VLS2/RW | 729 mm | VLS2/SRW | 739 mm | VLS2/LW | 729 mm | VLS2/SLW | |
| L | oad Bearing Capacity | 230 kg | | 300 kg | VL3Z/CVV | 300 kg | VLS2/SCW | 225 kg | VL3Z/RVV | 225 kg | VL32/3KW | 225 kg | VL3Z/LVV | 225 kg | V L32/3LVV |

VLS2/CT

Under Counter Prep Station Specifications

| PREP STATION + COVER TOP (T) | High Castor Base (HC) | | Standard Castor Base (C) | | Small Castor Base (SC) | | Rollers & Feet Base (R) | | Small Rollers & Feet Base (SR) | | Locking Roller Base (L) | | Small Locking Roller Base (SL) | |
|---------------------------------|--------------------------|----------|-----------------------------|---------|---------------------------|-------------------------|----------------------------|---------|-----------------------------------|----------|----------------------------|---------|-----------------------------------|----------|
| Finished Height | 846 mm | VLS2/HCT | 775 mm | VLS2/CT | 754 mm | 754 mm 0 kg VLS2/SCT | 730 mm | VLS2/RT | 720 mm | VLS2/SRT | 730 mm | VLS2/LT | 720 mm | VLS2/SLT |
| Load Bearing Capacity | 0 kg | | 0 kg | VL32/C1 | 0 kg | | 0 kg | | 0 kg | | 0 kg | | 0 kg | |